

New



The 118MAX hammer provides best-in-class power, superior ergonomics and reduced vibration to maximize operator comfort and productivity. It is perfect for exhaust system work, bodyshop applications, scrapping rust, bolt and rivet cutting as well as metal panel cutting.

- Up to 2 500 blows per minute.
- Alloyed steel barrel and heat-treated piston ensures longer life.
- Vibration reduction technology significantly increases user comfort and productivity.
- Quick change retainer provides fast and easy chisel change.
- Rubber handle grip offers great operator comfort and protects from cold air.
- Variable-speed lever allows precise delivery of power and speed.
- 360° swivel inlet helps eliminating twisted hoses.
- Through-handle exhaust directs air away from the operator.
- Tool also available as kit with: quick-change retainer and 5 chisels.

Specifications at 6.2 bar (90 psi)

Part Number	118MAX
Ordering number	47124490
Part Number (kit)	118MAXK
Ordering number (kit)	47125877
Shank type	round
Shank size	0.401 in / 10.2 mm
Other available versions:	
- hexagonal shank	118MAXH
- hexagonal shank and chisels	118MAXHK

PERFORMANCE

Piston bore	3/4 in / 19 mm
Piston stroke	3-1/2 in / 89 mm
Blows per minute	2 500

AIR SYSTEM

Air Inlet (NPT)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	2.90 CFM / 82.1 L/min
Air consumption at load	2.98 CFM / 84.4 L/min

NOISE & VIBRATION

Sound pressure / power (ISO15744)	94.7 / 105.7 dB(A)
Vibration level / measurement uncertainty (ISO28927)	5.7 / 2.3 m/s ²

WEIGHT & DIMENSIONS

Tool weight	4.6 lb / 2.1 kg
Tool dimensions (L x W x H)	12.4 x 2.2 x 6.9 in / 314 x 56 x 175 mm
Shipping weight (tool only)	5.9 lb / 2.7 kg
Shipping weight (kit)	8.8 lb / 4.0 kg
Shipping dimensions (tool only) (L x W x H)	305 x 195 x 80 mm
Shipping dimensions (kit) (L x W x H)	445 x 310 x 90 mm
UPC / EAN code (tool only)	6 63023 09948 4
UPC / EAN code (kit)	6 63023 09949 1
Origin	Made in Taiwan





116-K5
03808730
Chisels, round shank, 10.2 mm (5 pieces)



116-70
03820305
Chisel, round shank, 10.2 mm



116-88
03820271
Chisel, round shank, 10.2 mm



116-66
03820263
Chisel, round shank, 10.2 mm



116-87
03820297
Chisel, round shank, 10.2 mm



116-89
03820289
Chisel, round shank, 10.2 mm



9512
45563749
Quick change retainer



33104
91486330
Hose whip, 1/4" NPT, 6 mm inside diameter, 30 cm (1 ft)



77NMC2
88104070
7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)



IB6NMC2
88103015
IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



Quick Release Couplings
For the complete range, see our accessory catalogue.



Filters, regulators, lubricators
For the complete range, see our accessory catalogue.



10Z4
03875671
Oil, Class 1, no. 10, 0.12 L



Lubricants
For the complete range, see our accessory catalogue.